

## Workshop Fluke 45 Multimètre à double affichage

### Short description :

The Fluke 45 is a feature-rich 5-digit, 100 000 count meter that truly fits all applications and virtually any measurement need \_ on the workbench or in the field. Two multifunction displays and 16 different measurement capabilities allow wide ranging versatility at an affordable price. The Fluke 45 delivers high performance and flexibility for manufacturing test, depot and field service, as well as R&D applications.



- Multifunction vacuum fluorescent dual display allowing the user to measure two different parameters of the same signal from one probe
- True-rms voltage and current, including ac + dc
- RS-232 interface standard, IEEE-488.2 option
- Frequency measurement to 1 MHz
- dB measurements: 21 selectable reference impedances. From 2 to 8000, and audio power from 2? to 16?
- Compare (Hi/Low/Pass) function for quick in-tolerance tests
- 0.05% dc current accuracy for 4-20 mA current loop service
- Closed-Case Calibration: Calibration can be performed via the RS-232 (or optional IEEE-488.2) interface or manually from the front panel
- Optional FlukeView Forms, accessory software package; allows quick set-up and effortless communication between the Fluke 45 and a PC

**Localisation :** Electronic Workshop

**Personne(s) ressource(s) :** Souley Djadjandi,

**Site Web :** [www.uclouvain.be/welcome](http://www.uclouvain.be/welcome)

**Contact :** [info-welcome@uclouvain.be](mailto:info-welcome@uclouvain.be)